

FLEXIOUTDOOR

OUTDOOR KIOSK



TECHNICAL DATA

STRUCTURE

Powder coated aluminum profiles

MONITOR

Litemax
19" to 22"
1600 nits

TOUCHSCREEN

Zytronic anti-glare glass
Projected capacitive touch

CONTROLLER

Automatic temperature management
Emergency shutdown/startup
Unit surveillance
Noise cancelling fan system

PROTECTION & RESISTANCE

IP65 rating
Triple layer sealing
Removable dust filter
Standard heating unit 450W
4 ventilation fans
-20 to 40 degrees celcius

SECURITY

Dirak triple-point key locking system

MOUNTING

Concrete foundation

ACCESS

Front opening

RECOMMENDED MAX PC SIZE

Width: 200mm
Height: 200mm
Depth: 100mm

WEIGHT

Approximately 85 kg

FOOTSTAND

Powder coated aluminum



OPTIONS

BRANDING

Graphic laminate
Special RAL colours

HARDWARE

Payment interface
Card reader
Scanner QR - 2D - 1D
RFID scanner
Receipt printer
A4 printer
Intercom VOIP
Speakers
Camera
Keyboard
LED lighting
Antenna

ADDITIONAL WEATHER RESISTANCE

Aircondition unit
(Above 40 degrees celcius)
Heating unit 850W
(Below -20 degrees celcius)

ACCESS

Rear opening

4XPERTS GMBH

+49 (0) 2736 29432-80

Goethestraße 2a • 57299 Burbach • Deutschland

info@4xperts.de

www.infoterminals-kiosksysteme.de